## [27/July/2018 Updated Free Valid PassLeader 70q JN0-662 Exam Questions Ensure 100% Exam Passing (Part A)

New Updated JN0-662 Exam Questions from PassLeader JN0-662 PDF dumps! Welcome to download the newest PassLeader JN0-662 VCE dumps: https://www.passleader.com/jn0-662.html (70 Q&As) Keywords: JN0-662 exam dumps, JN0-662 exam questions, JN0-662 VCE dumps, JN0-662 PDF dumps, JN0-662 practice tests, JN0-662 study guide, JN0-662 braindumps, Service

Provider Routing and Switching, Professional (JNCIP-SP) Exam P.S. New JN0-662 dumps PDF: https://drive.google.com/open?id=18okRParXHon70E6eiz4CYPCamBLZuDsV P.S. New JN0-361 dumps PDF: https://drive.google.com/open?id=1xx4HdZ\_CTaUaTyfX\_xp10wDN10jHXZPh P.S. New JN0-102 dumps PDF: https://drive.google.com/open?id=0B-ob6L\_QiGLpSmYwaTA1elptQUE NEW QUESTION 1Which two types of LSAs have a domain scope? (Choose two.) A. Type 7B. Type 2C. Type 10D. Type 5 Answer: CD NEW QUESTION 2You are asked to configure a new Layer 3 VPN. In this scenario, which routing-instance type must be used? A. vplsB. evpnC. vrfD. 12vpn Answer: C NEW QUESTION 3Which authentication strategy authenticates IS-IS hello PDUs only? A. interface authenticationB. area authenticationC. domain authenticationD. level authentication Answer: D NEW QUESTION 4Which transport mechanism is required for Layer 3 VPNs? A. GREB. VXLANC. IPsecD. MPLS Answer: D NEW QUESTION 5You are asked to configure PIM-SM in your network. Your implementation must allow for load sharing between redundant RPs and, should an RP failure occur, the RP failover time should be minimized. Which two configuration tasks are required in this scenario? (Choose two.) A. Configure MSDP peering sessions between the routers designated as RPs.B. Configure the shared anycast address on the RPs as the primary address on the loopback interface.C. On the routers designated as RPs, configure the shared anycast address on the loopback interface.D. Configure at least two static RPs and bundle them in an RP redundancy group under [edit protocols pim]. Answer: BD NEW QUESTION 6In a carrier-of-carrier VPN model, which type of network layer reachability information is used for the MP-BGP signaling between CE and PE routers? A. flowB. labeled-unicastC. unicastD. inet-vpn Answer: DExplanation: In a Carrier-of-Carrier VPN environment, specify the inet-vpn address family and unicast traffic type to enable BGP to carry IPv4 network layer reachability information (NLRI) for VPN routes. http://www.juniper.net/documentation/en\_US/junos15.1/topics/example/mpls-vpn-option2-configuration.html NEW QUESTION 7 You want to add a new OSPF area to your existing OSPF network, however, this area will not be directly connected to Area 0. Which feature would you use to complete this task? A. a routing policyB. not-so stubby areaC. virtual linkD. Type 10 LSA Answer: C NEW QUESTION 8Which statement is correct regarding BGP route reflectors? A. The route reflectors must have a private AS number.B. The route reflectors must have an EBGP peering session between each other.C. The route reflectors must have a cluster ID configured.D. The route reflectors must have a different AS number than the clients. Answer: CExplanation: https://www.juniper.net/documentation/en\_US/release-independent/nce/topics/example/routing-protocol-bgp-security-route-reflector -configuring-cli.html NEW QUESTION 9You want to use IS-IS on a GRE interface where the underlying Layer 3 MTU is 1500. Which statement is correct in this scenario? A. IS-IS can be used because every IS-IS interface must be capable of transmitting packets at least as large as 1476 bytes, and the GRE header is 24 bytes.B. IS IS can be used, but the networking device directly attached to the circuit must be capable of fragmentation.C. IS-IS cannot be used, but the router can enable a GRE key that serves the same function as IS-IS.D. IS-IS cannot be used because the IS-IS hello is not allowed to be fragmented and has the DF bit set. Answer: BExplanation: https://kb.juniper.net/InfoCenter/index?page=content&id=KB7848 NEW QUESTION 10You are asked to deploy VPLS in your network as a new service for several customers, and you must identity the configuration and provisioning requirements for your customers. Which two statements are correct in this scenario? (Choose two.) A. CE interfaces facing the service prowler must be Ethernet interfaces.B. VLAN IDs defined on CE interfaces must be the same on both ends unless otherwise negotiated.C. CE interfaces facing the service provider must be Layer 3 interfaces.D. PE interfaces facing the core must have VPLS encapsulation enabled. Answer: AB NEW QUESTION 11Which message type initiates the BGP session? A. updateB. openC. keepaliveD. notification Answer: BExplanation: https://www.juniper.net/documentation/en\_US/junos/topics/concept/bgp-routing-messages-overview.html NEW QUESTION 12 Which two LSA types are permitted in an OSPF stub area? (Choose two.) A. Type 1B. Type 2C. Type 4D. Type 5 Answer: ABExplanation: Stub areas can contain type 1, 2, and 3 LSAs. A default route is substituted for external routes. NEW QUESTION 13Which two routes use a proper route distinguisher? (Choose two.) A. 192.168.0.1:12:10.1.0.0/16B. 12345:12:10.1.0.0/16C. 192.168.0.1:10.1.0.0:12/16D. 12345:10.1.0.0:12/16 Answer: AB NEW QUESTION 14Which neighbor state indicates that two BGP neighbors have full connectivity? A. IdleB. ConnectC. OpenConfirmD. Established Answer: D Download the newest PassLeader JN0-662 dumps from passleader.com now! 100% Pass Guarantee! JN0-662 PDF dumps & JN0-662 VCE dumps:

https://www.passleader.com/jn0-662.html (70 Q&As) (New Questions Are 100% Available and Wrong Answers Have Been Corrected! Free VCE simulator!) P.S. New JN0-662 dumps PDF:

https://drive.google.com/open?id=18okRParXHon70E6eiz4CYPCamBLZuDsV P.S. New JN0-361 dumps PDF:

https://drive.google.com/open?id=1xx4HdZ\_CTaUaTyfX\_xp10wDN10jHXZPh P.S. New JN0-102 dumps PDF:

https://drive.google.com/open?id=0B-ob6L QjGLpSmYwaTA1elptOUE