

## [Pass Ensure VCE Dumps Clear 400-201 Exam Easily With PassLeader Free 400-201 Dumps (21-40)]

PassLeader's 245q 400-201 vce dumps and pdf dumps help passing 400-201 exam! PassLeader nowadays provide the new version 400-201 exam questions with vce and pdf for free download, the latest 400-201 study guide and practice test tell you all details about exam 400-201, you can acquire the 400-201 certification easily by learning PassLeader's 245q 400-201 premium vce file and pdf dumps. Now visit [passleader.com](#) and download free 400-201 exam dumps and you will pass 400-201 exam the other day.

**keywords: 400-201 exam,245q 400-201 exam dumps,245q 400-201 exam questions,400-201 pdf dumps,400-201 practice test,400-201 vce dumps,400-201 study guide,400-201 braindumps,Cisco CCIE Service Provider Written Exam v4.0/v4.1**

Why Not T

Pass4su

↓  
Not Availabl  
Not In Stoc

QUESTION 21 What IOS commands display MPLS label mapping on an LSR? A. Show mpls ldp parameters B. Show mpls ldp bindings C. Show mpls forwarding-table D. Show mpls ldp discovery E. Show mpls ldp neighbor detail Answer: B QUESTION

22 Drag and Drop Questions

Drag and drop the appropriate AFISAFI description on the left to the corresponding identifier on the right.	
VPNv6	1/1
VPNv4	2/1
IPv4 Unicast	1/128
VPLS	2/128
IPv6 Unicast	2565

Answer:

Drag and drop the appropriate AFISAFI description on the left to the corresponding identifier on the right.	
VPNv6	IPv4 Unicast
VPNv4	IPv6 Unicast
IPv4 Unicast	VPNv4
VPLS	VPNv6
IPv6 Unicast	VPLS

QUESTION 23 Refer to the exhibit. The vrf MAINT has been provisioned and used by the Service Provider management network. The engineer discovers that syslog messages are not being received on the syslog server. IP reachability has been validated using ping. Which issue in the configuration must be corrected?

### Router PE-1

```
config t
ip vrf MAINT
  rd 200:1
  route-target import 100:1
  route-target export 100:1
  exit
!
interface FastEthernet/0/0
ip vrf forwarding MAINT
ip address 10.10.100.2 255.255.255.0
no shut
exit
!
logging on
logging host 10.10.100.100
logging trap debugging
end
```

[www.passleader.com](#)

A. logging on must include the vrf MAINT keyword.B. logging host must include the vrf MAINT keyword.C. The logging facility must be configured for syslog processing.D. The route targets that are configured do not match the route distinguisher.

Answer: BExplanation: [http://www.cisco.com/c/en/us/td/docs/ios/12\\_2sr/12\\_2sra/feature/guide/srvrflsg.html#wp1059076](http://www.cisco.com/c/en/us/td/docs/ios/12_2sr/12_2sra/feature/guide/srvrflsg.html#wp1059076)

QUESTION 24Which are the three header fields that affect how Equal-Cost Multipath hashes traffic flow into interface groups? (Choose three.)

A. source MAC addressB. source portC. source IP addressD. destination IP addressE. IP protocol ID  
destination MAC address Answer: BCD

QUESTION 25An R1 router requires an equal load balancing to reach the prefix 192.168.0.0/16 over two exit points: through R2 and R3 routers. Which two options must be configured on the R1 router to achieve this goal? (Choose two.)

A. The BGP maximum path feature must be configured on R1.B. The BGP PIC core must be enabled on R1C. Weight, local-pref, MED, as-path length, origin, and the BGP next-hop IGP cost must be the same for the R2 and R3 IBGP updates to R1.D. The BGP Link Bandwidth feature must be applied on R1.E. BGP extended community exchange must be enabled between IBGP neighbors. Answer: AC

QUESTION 26A company is deciding between an HVR and SVR solution in order to finalize a virtualization project proposal. Which is an advantage of a HVR solution versus a SVR solution? A. A HVR solution implements dedicated data plane resources.B. A HVR solution implements shared control plane resources.C. A HVR solution introduces significant contention of resources.D. A HVR solution implements dedicated chassis resources. Answer: A


QUESTION 27Which three of these are optical channel data unit (ODU) overhead fields? (Choose three) A. general communication channel 0 (GCC0)B. section monitoringC. reserved (RES)D. general communication channels 1 and 2 (GCC1 GCC2)E. tandem connection monitoring activation deactivation (TCM ACT) Answer: CDE

QUESTION 28Which three modes are the operating of HDLC? (Choose three) A. asynchronous balanced mode (ABM)B. normal response mode (NRM)C. normal peer mode (NPM)D. asynchronous client mode (ACM)E. asynchronous response mode (ARM) Answer: ABE

Explanation: Asynchronous response mode is an HDLC addition[1] for use over full-duplex links. While retaining the primary/secondary distinction, it allows the secondary to transmit at any time. Asynchronous balanced mode added the concept of a combined terminal which can act as both a primary and a secondary. There are some subtleties about this mode of operation; while many features of the protocol do not care whether they are in a command or response frame, some do, and the address field of a received frame must be examined to determine whether it contains a command (the address received is ours) or a response (the address received is that of the other terminal).

QUESTION 29BGP best route selection process is based on what? A. path attributes B. lowest costC. highest bandwidthD. lowest delayE. lowest hop-count Answer: A

QUESTION 30Refer to the exhibit. In the short-pipe QoS mode, this customer has QoS control for which two links? (Choose two.)



A. aB. cC. dD. bE. e Answer: AE

Why Not Try **PassLeader** New Premium 400-201 Exam Dumps?

<b>Pass4sure</b> Not Available Not In Stock	<b>PL PassLeader</b> Leader of IT Certifications 245 Q&As Price: \$99.99 Coupon Code -- CELEB	<b>TEST KING</b> Not Available Not In Stock
---	---	---

BONUS !!!  
Free VCE Player

<http://www.passleader.com/400-201.html> QUESTION 31Cisco IOS XR software is partitioned into three planes: control, data, and management. Which three of these belong to the data plane? (Choose three.) A. XMLB. RIBC. FIBD. QoSE. PFI


Answer: CDE QUESTION 32A network engineer is responsible for implementing a solution with Cisco IOS XR Software that insures continuous forwarding during a control plane failure. Which two technologies should the engineer consider? (Choose two.)

A. TE FRRB. IP FRRC. graceful restartD. BFDE. NSR Answer: CE

QUESTION 33What are three main characteristics of mLDP that differ from RSVP-TE? (Choose three.) A. The LSPs are built from tailend to headend.B. The LSPs are built from

headend to tailend.C. It supports only P2MP LSPs.D. It supports both P2MP and MP2MP LSPs.E. Signaling is periodic.F. No periodic signaling is performed. Answer: ADFExplanation:

[http://www.cisco.com/c/dam/en/us/products/ios-nx-os-software/multicast-label-distribution-protocol-mldp/whitepaper\\_c11-598929\\_v1.pdf](http://www.cisco.com/c/dam/en/us/products/ios-nx-os-software/multicast-label-distribution-protocol-mldp/whitepaper_c11-598929_v1.pdf) QUESTION 34Which are the two purposes of the MPLS label value 1? (Choose two.) A. it is used for MPLS OAM packets.B. it indicates an implicit null label.C. it is used for VPNv6 packets.D. it is used to carry the QoS value in the label stack.E. it indicates an explicit null label.F. it indicates a router alert label. Answer: AF QUESTION 35Refer the exhibit. Two Autonomous Systems are enabled to support multicast. An engineer wants to set up configuration so that a multicast client at AS 100 can receive multicast traffic from the M-Server at AS 200. However, the RP announcements must be limited within each autonomous system site. Which Cisco IOS configuration achieves this goal?



A. On both ASBRs Eth0/0 and the no ip pim sparse-mode command.B. On both ASBRs add the ip pim send-rp-discovery scope 1 command.C. On both RPs add the ip pim send-rp-discovery scope 2 command.D. On both ASBRs Eth0/0 and the ip pim bsr-border command.E. On both ASBRs Eth0/0 and the ip pim dense-mode command.F. On both RPs add the ip pim bsr-border command. Answer: D QUESTION 36What is the main advantage of H-VPLS over VPLS? A. H-VPLS provides redundancy.B. H-VPLS provides security.C. H-VPLS improves the scalability.D. H-VPLS allows a broader use of protocols. Answer: C

QUESTION 37In a Layer 2 VPN service, which is the default behavior of an EVC-based platform with regards to VLAN manipulation? A. keeps the VLAN tag of the incoming frameB. attaches two VLAN tags to the incoming frameC. removes the VLAN tag from the incoming frameD. removes all the VLAN tags from the incoming frameE. sets the VLAN tag of the incoming frame Answer: A QUESTION 38Which of these is not a component of MPLS traffic engineering? A. trunk admission controlB. forwarding traffic to tunnelC. information distributionD. path selection, calculation, and setupE. traffic patterns prediction Answer: E QUESTION 39Which three statements about MPLS traffic engineering (MPLS TE) are true? (Choose three) A. MPLS TE supports admission controlB. MPLS TE tunnel traffic is a link attribute to compute the TE tunnel pathC. MPLS TE uses BGP extension to advertise link attributesD. MPLS TE provides protection capabilityE. MPLS TE uses RSVP to establish LSP Answer: ADE QUESTION 40Which three statements about BGP confederation and route reflectors are true? (Choose three) A. Clusters are used in confederation schemes to avoid loops.B. BGP network can have a confederation within a route reflector area.C. An internal BGP network cannot have a route reflector within a confederation.D. An internal BGP network can have a route reflector within a confederation.E. Clusters are used in route reflector schemes to avoid loops.F. BGP network cannot have a confederation within a route reflector area. Answer: DEF

Why Not Try **PassLeader** New Premium 400-201 Exam Dumps

<b>Pass4sure</b> Not Available Not In Stock	<b>PL PassLeader</b> Leader of IT Certifications BONUS !!! Free VCE Player 245 Q&As Price: \$99.99 Coupon Code -- CELEB	<b>TEST K</b> Not Available Not In Stock
---	---	--

<http://www.passleader.com/400-201.html>