

Passleader C4040-108 Braindumps Help You Pass Exam With 100% Money Back

Vendor: IBM Exam Code: C4040-108 Exam Name: Power Systems Enterprise Technical Support for AIX and Linux -v2

QUESTION 1 An administrator is managing a two node PowerHA cluster on AIX 7. The administrator needs to add a shared volume group made up of a single disk presented through redundant VIO Servers to each node. Running `cfgmgr`, one node configures the new disk as `hdisk9` while the other node configures the same disk as `hdisk10`. The company has a naming standard which requires cluster disk to be configured with the same device names on all nodes. A number of scripts have been coded for this standard and will fail as a result of the different `hdisk` names. Which of the following is the quickest way to fix this?

A. Update any scripts to determine the cluster disk automatically. B. Use the `rendev` command to rename the disks before they are used. C. User `migratepv` to reorder the disks on the second node to match the first. D. Remove the other disks and add one by one using DLPAR in the correct order. Answer: B

QUESTION 2 What is the main difference between VIO Server (VIOS) and Network Server Description (NWS) hosting options?

A. NWS can only host IBM i or AIX, whereas VIOS can only host AIX and Linux. B. VIOS can host either AIX or IBM i LPARs, whereas NWS can only host IBM i.

C. VIOS can virtualize both storage and network, whereas NWS can only virtualize storage.

D. NWS can only virtualize local storage, whereas VIOS can virtualize local and SAN storage. Answer: C

QUESTION 3 All Power 795 system racks must have door assemblies installed. Three distinct door styles are available. One of the options - the acoustical door kit - reduces the noise emissions from the system. What attributes are improved by the other 2 door styles?

A. Weight, height B. Depth, security C. Depth, temperature

D. Height, temperature Answer: C

QUESTION 4 After upgrading their HMCs to the V7R720 release, a customer was planning to consolidate HMCs by taking advantage of the raised limit for maximum managed LPARs. They have found two POWER6 570s on which the password for both HMC and admin UserIDs has been forgotten. What ASMI UserID can the customer use, when directed by IBM Support, to reset the forgotten passwords?

A. `ibm` B. `root` C. `padmin` D. `celogin` Answer: D

QUESTION 5 A regional data center has experienced a disaster requiring the shared-processor LPARs running AIX on Power servers to be temporarily restored to Power servers in the disaster recovery data center (DRDC). The administrator has been asked to prepare an estimate of the number of cores that will need to be activated via Capacity on Demand on the target DR systems. The administrator has access to recently-collected `vmstat` data for each of the LPARs as well as the hardware configuration of the servers that hosted the LPARS, but does not have access to the individual LPAR profile configurations. Which of the following CPU elements from the `vmstat` output will allow the administrator to make an estimation of the core activation requirements?

A. `us` B. `sy` C. `wa` D. `ec` E. `pc` Answer: E

QUESTION 6 An administrator is attempting to diagnose a reported performance issue within a volume group. When trying to use the `lvmstat` command against a logical volume within the volume group, the following error is reported: `:0516-1309 lvmstat: Statistics collection is not enabled for this logical device.` The administrator does not want to enable collection across the whole volume group. How can collection be enabled on a single logical volume?

A. `chlv -s [lvname]`

B. `lvmo -L [lvname] -a` C. `lvmstat -l [lvname] -e` D. `chdev -l [lvname] -a stat=true` Answer: C

QUESTION 7 An administrator has logged into his HMC via `ssh` and is the only person using the HMC at this moment. When trying to open a terminal session to one of his LPARs using the `vtmenu` command, but only receives the error message: `A terminal session is already open for this partition. Only one open session is allowed for a partition.` Which command must be run in order to solve this problem?

A. `rmvterm` B. `termtask`

C. `vtmenu -k` D. `mkvterm -f` Answer: A

QUESTION 8 Which was the first release of IBM i to support Multipath I/O (MPIO) at the client LPAR level, when the same storage is served from redundant VIO Servers?

A. 6.1.0 B. 6.1.1 C. 7.1.0 D. 7.1.1

Answer: A

QUESTION 9 An administrator uses the `nmon` monitoring program on AIX LPARs and wants to use it on a newly installed LPAR running SLES11. Where can the administrator obtain `nmon` for the Linux LPAR?

A. From PowerVM LX86 B. From the SLES11 distribution

C. From the SourceForge website. D. From the AIX Toolbox for Linux Applications

E. From AIX as a Common Object File Format (COFF) Answer: C

QUESTION 10 A system administrator is preparing to restore a VIO Server (VIOS) partition with a backup that resides on a Network Install Manager (NIM) server. The VIOS backup image `ioslevel` is `FP24` (2.2.0.10-FP24). The NIM server has an `lpp_source` at `oslevel 6100-05-06-1034`, and a `SPOT` at the same level. In addition to the

VIOS backup image, which of the following NIM resources will be required in order to properly restore the VIOS backup image?
A. The existing lpp_source and SPOT B. A SPOT created from the existing VIOS backup C. A SPOT created from the the existing lpp_source D. The existing lpp_source and a SPOT created from the existing VIOS backup Answer: B QUESTION 11 An administrator has configured a system to provide resilient networking through the use of SEA failover. The administrator wants to know if the SEA for one VIO server, ent10, is the active adapter. Which of the following commands could the administrator use to determine the status of ent10?
A. entstat -net ent10 B. lsmmap -net -dev ent10 C. seastat -liststat ent10 D. netstat -cdlistats ent10 Answer: C QUESTION 12 A system administrator notices that an AIX partition can't ping its default gateway. The LPAR is connected to the network using Shared Ethernet Adapter (SEA). A partial output from the entstat command displays:

```
Virtual I/O Ethernet Adapter (I-lan) Specific Statistics:
-----
RQ Length: 4481
Trunk Adapter: True
Priority: 1 Active: True
Filter MCast Mode: False
Filters: 255
Enabled: 0 Queued: 0 Overflow: 0
LAN State: Operational

Hypervisor Send Failures: 150
Receiver Failures: 150
Send Errors: 0
Hypervisor Receive Failures: 0

Invalid VLAN ID Packets: 17391

LLAN Attributes: 00000000000003103 [00000000000003102]

Port VLAN ID: 201
VLAN Tag IDs: 812
```



Based on the output, what is the probable cause of the problem?
A. The Trunk Adapter parameter is set to True. B. The Port VLAN ID and VLAN Tag ID are different. C. IEEE 802.1Q support is disabled in the profile of the VIO Server. D. VLAN 812 is missing from the network switch configuration. Answer: B QUESTION 13 A system administrator must provide network access to a single VLAN for multiple partitions on a Power 795 server. The Power 795 server has a pair VIO Server (VIOS) partitions, with a Shared Ethernet Adapter (SEA) in each one. Each SEA will use a single-port Ethernet adapter as a backing device. Both SEAs must support network traffic so both adapters are used simultaneously. Network service must be resilient. All client partitions must be able to maintain network access to this VLAN through either VIOS partition if the other VIOS partition fails or is taken out of service. Which of the following configurations would satisfy this goal?
A. The SEAs are both connected to the same virtual switch. Both SEAs are configured for SEA failover. The client LPARs are configured with one virtual Ethernet adapter B. The SEAs are each connected to separate virtual switches. Both SEAs are configured for SEA failover. The client LPARs are configured with one virtual Ethernet adapter. C. The SEAs are both connected to the same virtual switch. Neither SEA is configured for SEA failover. The client LPARs are configured with NIB on two virtual Ethernet adapters. D. The SEAs are each connected to separate virtual switches. Neither SEA is configured for SEA failover. The client LPARs are configured with NIB on two virtual Ethernet adapters. Answer: D QUESTION 14 An administrator attempts to migrate a running LPAR using the 'migr_lpar' command. What task will help the administrator determine the cause of the errors?
A. Validate the configured attributes on the Properties tab of the LPAR profile. B. Validate that the VIO servers have the Mover Service Partition (MSP) attribute set. C. Validate that the required CPU entitlements are available on the destination server. D. Validate that the Logical Memory Block (LMB) size is consistent between both source and destination. Answer: B QUESTION 15 An administrator who manages systems in a remote 'lights-out' data center has been sent a set of AIX device drivers for some storage arrays. The software was sent by email from the third party manufacturer, in the form of an ISO image. What is the quickest and easiest way to install the drivers?
A. Using a PC, open a browser window onto the HMC 'updates' page. Select the ISO file on the PC and follow the on-screen instructions B. Write the ISO image to a CD and place it in a drive on the server. Follow the manufacturer's documentation to complete the installation C. Transfer the ISO image to a temporary

directory on the AIX system cd into the directory and run 'inutoc' followed by 'smitty install' D. Copy the ISO image to AIX and mount it using the 'loopmount' command Install from the mounted filesystem using the third party guidelines

Answer: C [Passleader C4040-108 Braindumps](#) Help You Pass Exam With 100% Money Back

